

## Product Specifications

### Physical Specifications

Physical Dimension 180 x 160 x 65 mm (L x B x H)

Weight 1 kg

### Performance Specifications

Flow Rate 0.1 – 50 ml/s

Void Volume Up to 1000 ml

Volume Accuracy  $\pm 2\%$  of voided volume

Modes Manual, Auto

Parameters Measured Maximum flow rate, Average flow rate, Voided volume, Voiding time, Flow time, Time to max, Hesitancy time

Sensor Load cell with 3 kg capacity

Alarms Jar displaced, Device overloaded, Device disconnected, Battery low, Battery depleted, Sensor failure

Ingress Protection IPX4

Data Communication Bluetooth

### Battery

Type 4 rechargeable AA batteries

Backup 10 days

Recharging Time 6 hrs

### Accessories

Batteries, Charger, Tablet, Uroflowmeter stand, Funnel, Collecting jar, Micturition chair, Tablet Stand

### Warranty

1 year from the Date of Shipment

### vTitan Corporation Private Limited

New Woodlands Building, Estancia IT Park,  
Plot No. 140,151 Vallancheri Village,  
Chengalpattu District,  
Tamil Nadu - 603202, India.

[www.vtitan.com](http://www.vtitan.com)

[sales@vtitan.com](mailto:sales@vtitan.com)

©2024 vTitan Corporation Pvt. Ltd.

980-1082 Rev 05










# Accuflow® Uro

Uroflowmeter

Uro-0102

- ◆ Compact & Portable
- ◆ Enhanced safety & simplicity
- ◆ Hassle-Free Operation
- ◆ Wireless Data Acquisition
- ◆ Real - time Display
- ◆ User-friendly

## Accuflow Uro Key Features

-  Lightweight
-  High precision load cell sensor
-  Adjustable Urine Density and Flow Scale
-  Pre-configurable diagnostic codes
-  Wireless and Real-Time Data Acquisition
-  Sharing of report via email and other applications
-  Generation of detailed reports with patient data, results and nomograms

## User-Intuitive Application



### Automatic Device Configuration

Open the app to automatically pair with the device via Bluetooth




### Effective Verification of Calibration

Provision for verifying the calibration to ensure high performance accuracy




### Auto / Manual Modes of Operation

Auto Start / Stop feature that assures ease of use  
Manual mode to calculate hesitancy




### Comprehensive Reports

View detailed reports for current as well as previous tests  
Wirelessly print or share the generated report  
via e-mail or other applications



### Prompt Visual Alarms

Lucid alarm indications on the app to alert the user at the right time



### Help Section

Watch Demo videos, view FAQs, Instructions For Use and other resources to know more about the device